# MagicQ DIN



Product Code: CS100016

The full power of MagicQ software in a DIN rail mount solution.

MagicQ DIN supports all MagicQ features, including scheduled events, UDP, OSC and other remote protocols, making it ideal for cabinet installation in control rooms and suitable for theatres, houses of worship, and any venue requiring powerful control that offers the advanced capabilities of MagicQ such as pixel mapping and multi-element fixture control.

Its 24 universes of DMX output are expandable to 48 and connectivity features include two RDM-enabled DMX ports, inbuilt Wi-Fi for programming and remote control, and four 10Scene ports for connecting up to forty 10Scene wall plates.

## **Specifications**

### **Hardware Specification**

- Universes Supported: 24\* expandable to 48
- Direct DMX Outputs Pheonix Screw Terminal: 2
- External Monitor: 1920 x 1080 HDMI
- Inbuilt Wi-Fi: Yes
- Network Port: 1
- USB Ports: 2
- · Power Input: 12v DC

### **Software Specifications**

- Max Number of DMX Channels: 12288 \*expandable to 24576
- Max Number of Fixtures Supported: 12288 \*expandable to 24576
- Max Number of Cues: 5000
- Max Number of Cue Stacks: 2000
- Max Number of Groups: 5000
- Max Number of Palettes: 4096
- Number of Media Server Layers Supported: 50 (each dif ferent content)
- OSC Supported: Yes
- RDM for remote configuration and patching.
- Heads Personality library of over 48,000 head files.
- Built in FX generator
- Colour picker and Gel inbuilt Gel library

#### Included Accessories:

- Wi-Fi Antenna: 1
- DIN Rail Mount Clips: 2
- 10Scene Connectors: 4
- 12v Power Supply: 1

#### **Rack Weights and Dimensions:**

- Width : 200mm (7.8 inches)
- Depth: 165mm (6.5 inches)
- Height: 40mm (1.6 inches)
- Weight: 0.65kg (1.43lb)

### Boxed Weights and Dimensions:

- Width: 268mm (10.5 inches)
- Depth: 220mm (8.7 inches)
- Height: 130mm (5.1 inches)
- Weight: 1.04kg (2.29 lb)

ChamSys